





PRODUCT BROCHURE

ΕN

ACCU-LINK® ADJUSTABLE LINK V-BELT

Accu-link[®] is Megadyne's link belt, created and developed as an alternative to classical rubber V-belts. Megadyne's Accu-link[®] combines superior strength and durability with quick and easy assembly and installation. The original concept is to give a fast replacement to classical V-belts in case of a break.

Today, Accu-link® is used in a very wide range of applications as original equipment.

Accu-link[®] is a link belt: this means it is made of several links assembled together. Thanks to this, belts can have any length just by modifying the number of links.

Links are made with a polyurethane material, reinforced by a multilayer woven polyester fabric. State-of-the-Art manufacturing produces a high-quality link design which yields superior performance. Accu-link[®] is precision ground for a smooth side edge and section, which leads to a smooth, silent, low vibrating belt.

MAIN FEATURES AND ADVANTAGES

• EASY TO ASSEMBLE

Accu-link® can be assembled without tools and in a matter of seconds.

EASY TO INSTALL

Accu-link[®] can be adapted to any length; in case of difficult layout or when taking the drive apart would take too long. Accu-link[®] can be installed open and closed afterwards, in a very easy and fast way.

SMALL INVENTORY

With one roll of Accu-link[®] it is possible to get any length of classical V-belts; with one roll per section, inventories will be much smaller, easier and less expensive to manage.

HIGH POWER RATE

Accu-link®has power ratings similar to classical V-belts.

- HIGH RESISTANCE TO ENVIRONMENT
 Thanks to its state-of-the-art materials, Accu-link[®] can withstand salt, chemicals, oils and grease. This increases the lifetime compared to standard rubber V-belts.
- HIGH TEMPERATURE RESISTANCE Accu-link[®] can operate in a wide range of temperatures: -25 °C / +80 °C (-13 °F / 176 °F)
- HIGH RESISTANCE TO HARSH ENVIRONMENTS
 Accu-link® is suited for harsh environments where it can outlast standard rubber V-belts.
- QUIET AND SMOOTH RUNNING
 Due to the independent link design, Accu-link[®] runs quieter and smoother than a classical V-belt.

APPLICATIONS

Accu-link® belts can be used in a wide range of applications.

The following table lists some of the main applications where Accu-link® Adjustable Link V-belts are widely used with the advantages compared to classical rubber V-belts.

APPLICATIONS	MAIN ADVANTAGES		
Marine industry	Higher resistance to salty and greasy environments Reduced inventory		
Air handling	Easier and quicker to install		
Metal and wood working machines	Reduced noise, reduced vibration		
Poultry industry	Enhanced resistanceto harsh environments		
Agriculture	Enhanced resistance to typical agri-environments		
Rolling conveyor	Easier and quicker to install Better performing in case of pulley misalignment		
Glass industry	Non staining		
Tiles and marble conveyor	Easier and quicker to install Enhanced resistance to harsh environments		





Accu-link[®] belts are available in Z/3L, A/4L, B/5L and C sections. Accu-link[®] can work on standard pulleys for V-belts. Megadyne can supply open end Accu-link[®] in carton boxes or endless belts in light carton sleeves.

	Z/3L	A/4L	B/5L	С	
Belt weight g/m (+/-1,5)	43,0	76,5	117,5	178,5	
Min pulley diameter (mm)	45	80	140	225	
Service temperature range	-25 °C / +80 °C (-13 °F / 176 °F)				
Standard roll lengths (ft)	25-100	25-100	25-100	25-50	
Standard sleeve lengths (ft)	5	5-6	6	5	

Download the e-book with Technical Calculation:



INSTRUCTIONS

MEASURING-



1. Pull the belt tight around the sheaves to check the needed length, overlapping the last two tabs with two holes in matching.

2. Count the number of links and remove one link every 24 for Z/3L, A/4L and B/5L sections, and one link every 20 for C section to get the proper installation tension.

3. For multiple belt drives, be ensure that each belt has the same number of links.

ASSEMBLING



1. Holding the belt with the tabs upwards, let the tab of one belt's end get through two links at once. (three if C section)

DISASSEMBLING



1. Put the belt with the tabs upwards and bend it as much as possible.



2. Flexing the belt as much as needed, twist and insert the second tab through the end link.



3. Ensure that tab will stay transversally to the belt's running direction; reverse the belt upside down to let it running on the tab side.



2. Twist one tab 90° to make it parallel to the belt; in this way you can pull the end of the link over the tab.

NOTE: Unlike conventional V-belts, Accu-link® can be rolled on to pulleys - no cord to break

3. Rotating the belt by 90° you can

3. Rotating the belt by 90° you can now easily pull one belt's end away from the other one.

INSTALLATION

- 1. Be sure that the belt has the tabs on the inner side: the belt has to run with the tabs oppositely facing the running direction
- 2. Fit the belt in the nearest groove of the smallest sheave and then roll the belt onto the larger sheave; for multiple belts drive, repeat the operation on all the grooves
- 3. Always make sure that belts look pretty tight and tabs are still in the correct position.

If it is easy to move the engine, you might install the belt in the following way:

- 1. Set the engine in mid position of its adjustment range and mark this position clearly
- 2. Check the belt's length as previously shown
- 3. Move the engine forward to reduce the center distance
- 4. Install the belt as in "INSTALLATION" paragraph
- 5. Pull the engine back to the previously marked position.

RETENSIONING

As in any V-belt drive, Accu-link[®] belts require to check for tension after 24 h of full load operating time. If the belt is not tight enough, restore the tension by removing some link. Anyway, check the belt's tension periodically and restore tension.



Discover Your Local Contacts

The local partner of choice for sustainable power transmission belting solutions around the globe.



General contact information: Megadyne Via Trieste, 16 Via S. Lucia 114 - 10075 Mathi (Torino) Italy

Scan the QR code and find your local contact



This information is subject to alteration due to continuous development. Megadyne will not be held liable for the incorrect use of the above stated information. This information replaces previous information. All activities performed and services rendered by Megadyne are subject to general terms and conditions of sale and delivery, as applied by its operating companies.